

*Quick and energy saving*



## hs4c Beaver

---

### Highlights

---

**Opens automatically at completion of sealing cycle**

**Low energy lost:**

- ceramic iron
- power save mode

**Electronic timer**

**Electronic temperature control**

---

**The hs4c opens automatically**

---



### Opens automatically

Being as compact as the hs3c, the hs4c heat seal machine opens automatically at the end of the press cycle. No chance of sealing too long with the risk of scorching! The hs4c is Ideal for attaching identification labels, property marking and mending linens, in small to medium requirements.

### Dependable

Anywhere lacking a compressed air supply, the hs4c provides convenient and dependable heat seal capability. It marks linens with property mark transfers for theft deterrence and applies Thermopatch mending products with a strong, lasting bond. Employee and patient garments with heat sealed identification labels avoid mix-ups and simplify sorting.

### Specifications

<b>Power consumption</b>	115 volts	230 volts
<b>Power supply</b>	640 watts	640 watts
<b>Temperature</b>	69°F-446°F	20-230°C
<b>Machine height (open)</b>	19.3"	490 mm
<b>Machine height (closed)</b>	9.3"	240 mm
<b>Machine width</b>	7.5"	190 mm
<b>Machine depth (connections included)</b>	20.4"	520 mm
<b>Net weight</b>	57.3 lbs.	26 kg
<b>Press pad dimensions</b>	3.75" x 4.75"	95 x 120 mm
<b>Fuses</b>	6 amps	3 amps
<b>A-weighted noise level</b>	< 70 dB (A)	< 70 dB (A)

As a light, compact unit, the hs4c can be moved from place to place, exactly where it is needed.

---

Thermopatch Australia Pty Ltd	Australia	tel. +61 395325722	fax +61 395325652	e-mail <a href="mailto:marktpatchaust@bigpond.com.au">marktpatchaust@bigpond.com.au</a>
Thermopatch Canada Inc	Canada	tel. +1 519 748-5027	fax +1 519 748-1543	e-mail <a href="mailto:broussel@thermopatch.com">broussel@thermopatch.com</a>
Thermopatch European Headquarters	Netherlands	tel. +31 36 549 11 11	fax +31 36 532 03 98	e-mail <a href="mailto:sales@thermopatch.nl">sales@thermopatch.nl</a>
Ducker Ltd	United Kingdom	tel. +44 1539 722122	fax +44 1539 721000	e-mail <a href="mailto:fresh@ducker.co.uk">fresh@ducker.co.uk</a>
Thermopatch Corporate Headquarters	USA	tel. +1 315 446-8110	fax +1 315 445-8046	e-mail <a href="mailto:sales@thermopatch.com">sales@thermopatch.com</a>